(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 13 October 2005 (13.10.2005)

PCT

(10) International Publication Number WO 2005/095465 A1

(51) International Patent Classification⁷: 2/34, 10/00, B01J 8/20

C08F 2/00,

(21) International Application Number:

PCT/EP2005/001000

(22) International Filing Date: 31 January 2005 (31.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

04100856.6 3 March 2004 (03.03.2004) EP 60/551,179 8 March 2004 (08.03.2004) US

- (71) Applicant (for all designated States except US): BASELL POLIOLEFINE ITALIA S.P.A. [IT/IT]; Via Pergolesi, 25, I-20124 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MEI, Gabriele [IT/IT]; Viale Cavour, 144, I-44100 Ferrara (IT). BERTOLINI, Stefano [IT/IT]; Via Matteotti, 77, I-60015-Falconara Marittima, Ancona (IT).
- (74) Agent: SACCO, Marco; Basell Poliolefine Italia S.p.A., Intellectual Property, P.le G. Donegani 12, I-44100 Ferrara (ΙΤ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR CONTROLLING THE POLYMER FLOW IN A POLYMERIZATION PROCESS

(57) Abstract: A method for controlling the flowability of polymer particles flowing downward in a densified form inside a polymerization reactor, in which one or more monomers are gasphase polymerized in the presence of a polymerization catalyst, the density of solid (Kg of polymer per m³ of reactor occupied by the polymer) being higher than 80% of the "poured bulk density" of the polymer, the method being characterized in that a liquid stream is continuously fed into the polymerization reactor at a mass flow rate per unity of reactor surface higher than 30 Kg/h m².